

# AQSync Air Quality Monitoring Station: Detailed Specifications

Instrument/Sensor Specifications (per manufacturer)	
<p><b>Ozone (O<sub>3</sub>)</b></p> <p><b>Measurement Method:</b> UV Absorbance at 254 nm  <b>Instrument:</b> 2B Technologies Model 108-L (FEM)  <b>Linear Range:</b> 0-100,000 ppb  <b>Precision:</b> 1.5 ppb or 2% of reading for 10-s avg  <b>Accuracy:</b> 1.5 ppb or 2% of reading  <b>Response Time:</b> 4 s for 2-s avg, 20 s for 10-s avg</p>	<p><b>Nitrogen Dioxide (NO<sub>2</sub>)</b></p> <p><b>Measurement Method:</b> Direct Absorbance at 405 nm  <b>Instrument:</b> Based on 2B Tech Model 405 nm NO<sub>2</sub>/NO/NO<sub>x</sub> Monitor (FEM for NO<sub>2</sub>)  <b>Linear Range:</b> 0-10,000 ppb  <b>Precision:</b> 0.5 ppb  <b>Accuracy:</b> 2 ppb or 2% of reading  <b>Response Time:</b> 20 s</p>
<p><b>Nitric Oxide (NO)</b></p> <p><b>Measurement Method:</b> Oxidation to NO<sub>2</sub> with O<sub>3</sub> followed by Absorbance of NO<sub>2</sub> at 405 nm  <b>Instrument:</b> 2B Tech Model 405 nm NO<sub>2</sub>/NO/NO<sub>x</sub> Monitor  <b>Linear Range:</b> 0-2,000 ppb  <b>Precision:</b> 0.5 ppb  <b>Accuracy:</b> 2 ppb or 2% of reading  <b>Response Time:</b> 20 s</p>	<p><b>Particulate Matter (PM<sub>1</sub>, PM<sub>2.5</sub>, PM<sub>10</sub>)</b></p> <p><b>Measurement Method:</b> Optical Particle Counter, right angle light scatter detection with sheath flow and heated inlet  <b>Instrument:</b> Met One Instruments Model 83214  <b>Range:</b> 0-320,000 particles per liter  <b>Minimum Particle Size:</b> 0.3 µm  <b>Accuracy:</b> 10%  <b>Response Time:</b> minimum 1 s</p>
<p><b>Carbon Dioxide (CO<sub>2</sub>)</b></p> <p><b>Measurement Method:</b> Non Dispersive Infrared (NDIR) Absorbance with Auto-Zeroing  <b>Instrument:</b> PP Systems CO<sub>2</sub> Gas Analyzer, Model SBA-5  <b>Linear Range:</b> 0-1,000 ppm  <b>Precision:</b> 1 ppm  <b>Accuracy:</b> 5 ppm  <b>Response Time:</b> 10 s</p>	<p><b>Carbon Monoxide (CO)</b></p> <p><b>Measurement Method:</b> Amperometry  <b>Linear Range:</b> 0-50 ppm  <b>Sensor:</b> Alphasense CO-A4  <b>Precision:</b> 0.02 ppm  <b>Accuracy:</b> 0.1 ppm  <b>Response Time:</b> 20 s</p>
<p><b>Total VOCs</b></p> <p><b>Measurement Method:</b> Photoionization Detector  <b>Sensor:</b> ION Science Mini-PID2 HS  <b>Measurement Range:</b> 0 to 3 ppm  <b>Sensitivity:</b> &gt; 600 mV per ppm  <b>Minimum Detection Limit:</b> 0.5 ppb  <b>Response Time:</b> &lt; 12 s</p>	

\*Option for SO<sub>2</sub> sensor; contact 2B Tech for information.

## Weather Station Specifications

(per manufacturer)

Gill Instruments MaxiMet 500GMX	Range	Accuracy
<b>Temperature</b>	-40 to +70 °C	±0.3 °C (at 20 °C)
<b>Pressure</b>	300 – 1100 hPa	±0.5 hPa (at 25 °C)
<b>Relative Humidity</b>	0 – 100% RH	±2 %RH (10 to 90 %RH)
<b>Wind Speed</b> (2-D Sonic Anemometry)	0.01-60 m/s (134 MPH)	±2% (0-30 m/s) ±3% ( >30 m/s)
<b>Wind Direction</b> (2-D Sonic Anemometry)	0-360 degrees azimuth	±3 degrees (to 40 m/s) ±5 degrees (40-60 m/s)

## System Specifications

<b>Weight</b>	54.7 lb, 24.9 kg (varies with modules chosen)
<b>Size</b>	25.5 H x 25.5 W x 10.3 D in (65 x 65 x 26.2 cm); height with weather station is 49 in (124.5 cm)
<b>Power</b>	35 watt (53 watt max during warmup) (varies with modules chosen)
<b>Data Transmission</b>	Cellular or WiFi to the Cloud; Ethernet option
<b>Sample Flow Rate</b>	~4 L/min (varies with modules chosen)